



ISOMETRIC VIEW


- STANDARD INLET PROVIDED WITH THINNED SECTIONS IN ONE LONG WALL AND BOTH SHORT WALLS.
- THINNED SECTIONS ARE 26" X 26", 2" THICK, AND LOCATED AT FLOOR LEVEL
- INSTALLER TO BREAK OUT THINNED SECTIONS AS NECESSARY TO ALLOW PIPE PENETRATIONS.
- PIPE TO BE GROUTED INTO INLET BOX BY INSTALLER.
- PLEASE CALL FOR SPECIAL APPLICATIONS.
- STANDARD CASTINGS FOR FRAMES AND GRATES DESIGNED FOR HS20-44 LOADING.
- CURB BACKS WITH ENVIRONMENTAL AWARENESS SYMBOL CAN BE PROVIDED.
- SCALE: NONE




D&L I-3517 FRAME & D&L I-3516 CURB BACK




D&L I-3386 FRAME (CONCAVE)




D&L I-9163 FRAME




D&L I-3516 GRATE NON DIRECTIONAL




D&L I-3386 GRATE NON DIRECTIONAL



D&L I-9163 GRATE



D&L I-3517 GRATE DIRECTIONAL



D&L I-3386 GRATE DIRECTIONAL



725 BRYAN STOCK TRAIL  
 CASPER, WYOMING 8260  
 Phone: (307)265-3100  
 Fax: (307)265-0013

DRAWN BY: MDB  
 DATE: 2-18-09  
 TYPE CC INLET  
 (2'-0" X 3'-0" X 3'-0")